



Printing date 10.04.2025 Version number 307 (replaces version 306) Revision: 10.04.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600245

· Trade name: Wood Lubricant E-COLL

· Article number: 4317784305594

UFI: ETYQ-Q41R-3C03-C83Y

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Chemical-Technical Products Division
- · 1.4 Emergency telephone number:

Poison Control Center Mainz - 24 hour emergency service - phone: +49 (0) 6131/19240

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)





Printing date 10.04.2025 Version number 307 (replaces version 306) Revision: 10.04.2025

Trade name: Wood Lubricant E-COLL

(Contd. of page 1)

### · Hazard pictograms





GHS02 GHS09

### · Signal word Danger

### · Hazard-determining components of labelling:

C9-12-Iso-alkanes

Hydrocarbons, C10-C12, isoalkanes, <2% aromatics

White mineral oil, petroleum

#### Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H411 Toxic to aquatic life with long lasting effects.

### · Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P273 Avoid release to the environment.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

## · 2.3 Other hazards

The mixture does not contain any substance with endocrine disrupting properties (< 0.1%).

### · Results of PBT and vPvB assessment

#### · PBT

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or does not fall under Annex XIII of Regulation (EC) 1907/2006 (< 0.1%).

#### · vPvB:

The mixture does not contain a vPvB substance (vPvB = very persistent, very bioaccumulative) or does not fall under Annex XIII of Regulation (EC) 1907/2006 (< 0.1%).

## **SECTION 3: Composition/information on ingredients**

### · 3.2 Mixtures

· **Description**: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)





Printing date 10.04.2025 Version number 307 (replaces version 306) Revision: 10.04.2025

Trade name: Wood Lubricant E-COLL

(Contd. of page 2)

· Dangerous components:		
CAS: 90622-57-4 EC number: 918-167-1 Reg.nr.: 01-2119472146-39-XXXX	C9-12-Iso-alkanes  Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413 EUH066	25-50%
EC number: 923-037-2 Reg.nr.: 01-2119471991-29	Hydrocarbons, C10-C12, isoalkanes, <2% aromatics  Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	25-50%
CAS: 8042-47-5 EINECS: 232-455-8 Reg.nr.: 01-2119487078-27-xxxx	White mineral oil, petroleum  Asp. Tox. 1, H304	10-<25%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Personal protection for the First Aider.
- · After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

## · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

### · After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

## · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

## · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

(Contd. on page 4)





Printing date 10.04.2025 Version number 307 (replaces version 306) Revision: 10.04.2025

Trade name: Wood Lubricant E-COLL

(Contd. of page 3)

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

· Additional information Cool endangered receptacles with water spray.

### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

· 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Use only in well ventilated areas.
- · Information about fire and explosion protection:



Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 5)





Printing date 10.04.2025 Version number 307 (replaces version 306) Revision: 10.04.2025

Trade name: Wood Lubricant E-COLL

(Contd. of page 4)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- $\cdot$  Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

## CAS: 8042-47-5 White mineral oil, petroleum

Dermal Long term value for employees 220 mg/kg bw/Tag (professional use)
Inhalative Long term value for employees 160 mg/m³ (professional use)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

· Hand protection



Material of gloves
 Nitrile rubber, NBR





Printing date 10.04.2025 Version number 307 (replaces version 306) Revision: 10.04.2025

Trade name: Wood Lubricant E-COLL

(Contd. of page 5)

Recommended thickness of the material: ≥ 0.4 mm

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

Colour:
 Odour:
 Odour threshold:
 Melting point/freezing point:

Colourless

 Characteristic
 Not determined.
 Undetermined.

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: -60 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

Kinematic: 23 °C - 4 mm (ISO 2431)

· **Dynamic:** Not determined.

· Solubility

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure at 20 °C:
 Not determined.
 2800 hPa

· Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

(Contd. on page 7)





Printing date 10.04.2025 Version number 307 (replaces version 306) Revision: 10.04.2025

Trade name: Wood Lubricant E-COLL

(Contd. of page 6)

• Explosive properties: Not determined.

· Solvent separation test:

· **VOC (EC)** % 84,60 %

VOC (EC) g/l

· VOCV (CH) 84,60 %

· Change in condition

· Drip point:

Oxidising propertiesEvaporation rateNot determined.Not applicable.

· Information with regard to physical hazard

classes

Explosives VoidFlammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

Void

May burst if heated.

· Oxidising gases Void · Gases under pressure Void Void · Flammable liquids · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable Void gases in contact with water · Oxidising liquids Void Void · Oxidising solids Organic peroxides Void · Corrosive to metals Void

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

Desensitised explosives

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- $\cdot$  10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.





Printing date 10.04.2025 Version number 307 (replaces version 306) Revision: 10.04.2025

Trade name: Wood Lubricant E-COLL

(Contd. of page 7)

### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics		
Oral	LD50	>5,000 mg/kg (rat) (OCED 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OCED 402)
Inhalative	LC50/4h	>5,000 mg/m³ (rat)
CAS: 8042-47-5 White mineral oil, petroleum		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- $\cdot$  STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 9)





Printing date 10.04.2025 Version number 307 (replaces version 306) Revision: 10.04.2025

Trade name: Wood Lubricant E-COLL

(Contd. of page 8)

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

16 05 04\* gases in pressure containers (including halons) containing hazardous substances

## **SECTION 14: Transport information**

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS

· IMDG AEROSOLS · IATA Aerosols

(Contd. on page 10)





Printing date 10.04.2025 Version number 307 (replaces version 306) Revision: 10.04.2025

Trade name: Wood Lubricant E-COLL

(Contd. of page 9)

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

·IMDG



Class
 Label
 2 Gases.
 2.1

·IATA



· Class 2 Gases. · Label 2.1

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: Yes

Symbol (fish and tree)
Special marking (ADR):
Symbol (fish and tree)

• 14.6 Special precautions for user Persons involved in the transport of dangerous goods

must be trained.

Safety regulations must be observed by all persons

involved in the transport.

Precautions must be taken to prevent damage.

Warning: Gases.

• EMS Number: F-D,S-U

· 14.7 Maritime transport in bulk according to IMO

**instruments** Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)Transport category2

(Contd. on page 11)





Printing date 10.04.2025 Version number 307 (replaces version 306) Revision: 10.04.2025

Trade name: Wood Lubricant E-COLL

(Contd. of page 10)

· Tunnel restriction code D

· IMDG

· Limited quantities (LQ)

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

## SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS09

· Signal word Danger

## · Hazard-determining components of labelling:

C9-12-Iso-alkanes

Hydrocarbons, C10-C12, isoalkanes, <2% aromatics

White mineral oil, petroleum

### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H411 Toxic to aquatic life with long lasting effects.

#### · Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P273 Avoid release to the environment.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

### · Chemical safety assessment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

(Contd. on page 12)





Printing date 10.04.2025 Version number 307 (replaces version 306) Revision: 10.04.2025

Trade name: Wood Lubricant E-COLL

(Contd. of page 11)

### · REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

### · Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

### · Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Other regulations, limitations and prohibitive regulations

**Employment restrictions:** 

Observe employment restrictions for young people ( 22 JArbSchG)

Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at: sdb@ede.de

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life. EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Product safety department

· Contact: sdb@ede.de

Date of previous version: 25.02.2022
Version number of previous version: 306

## Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

(Contd. on page 13)





Version number 307 (replaces version 306) Printing date 10.04.2025 Revision: 10.04.2025

**Trade name: Wood Lubricant E-COLL** 

(Contd. of page 12)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Aerosol 1: Aerosols – Category 1
Flam. Liq. 3: Flammable liquids – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

· \* Data compared to the previous version altered.

EU —