



Printing date 03.12.2024 Version number 306 (replaces version 302) Revision: 03.12.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier 600251

· Trade name: Spray adhesive that can be separated E-COLL

· Article number: 4317784514323

· UFI: 3XXQ-N44S-1C04-RU9A

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number:

Poison Control Center Mainz - 24 hour emergency service - phone: +49 (0) 6131/19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The labelling of an aspiration hazard (Asp.Tox.1 H304) is not required for aerosol dispensers and containers with a sealed spray device (Regulation (EC) 1272/2008, Annex 1,1.3.3). The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)





Printing date 03.12.2024 Version number 306 (replaces version 302) Revision: 03.12.2024

Trade name: Spray adhesive that can be separated E-COLL

(Contd. of page 1)

· Hazard pictograms



· Signal word Danger

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. P251

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

The product does not meet the PBT and vPvB classification criteria Contains no PBT and/or vPvB substances ≥ 0.1%, assessed according to REACH Annex XIII

- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description**: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8	dimethyl ether Flam. Gas 1A, H220 Press. Gas (Comp.), H280 EUH044	50-100%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	<1.25%





Printing date 03.12.2024 Version number 306 (replaces version 302) Revision: 03.12.2024

Trade name: Spray adhesive that can be separated E-COLL

	(Con	itd. of page 2)
CAS: 142-82-5 EINECS: 205-563-8 Index number: 601-008-00-2 Reg.nr.: 01-2119457603-38-xxxx	heptane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315; STOT SE 3, H336	<1.25%
CAS: 64742-49-0 EINECS: 265-151-9 Index number: 649-328-00-1 Reg.nr.: 01-2119475514-35-XXXX	hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cycloalkanes, < 5% n-hexane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	<1.25%
CAS: 108-05-4 EINECS: 203-545-4 Index number: 607-023-00-0 Reg.nr.: 01-2119471301-50-xxxx	vinyl acetate Flam. Liq. 2, H225 Carc. 2, H351 Acute Tox. 4, H332; STOT SE 3, H335	0.1-<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Keine besonderen Maßnahmen erforderlich.
- · After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.





Printing date 03.12.2024 Version number 306 (replaces version 302) Revision: 03.12.2024

Trade name: Spray adhesive that can be separated E-COLL

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- 6.2 Environmental precautions: No special measures required.
- · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Use only in well ventilated areas.
- · Information about fire and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

(Contd. on page 5)





Printing date 03.12.2024 Version number 306 (replaces version 302) Revision: 03.12.2024

Trade name: Spray adhesive that can be separated E-COLL

(Contd. of page 4)

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:		
CAS: 115-10-6 dimethyl ether		
IOELV Long-term value: 1920 mg/m³, 1000 ppm		
CAS: 141-78-6 ethyl acetate		
IOELV Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm		
CAS: 142-82-5 heptane		
IOELV Long-term value: 2085 mg/m³, 500 ppm		
CAS: 108-05-4 vinyl acetate		
IOELV Short-term value: 35.2 mg/m³, 10 ppm Long-term value: 17.6 mg/m³, 5 ppm		

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Short term filter device:

(Contd. on page 6)





Printing date 03.12.2024 Version number 306 (replaces version 302) Revision: 03.12.2024

Trade name: Spray adhesive that can be separated E-COLL

(Contd. of page 5)

Filter A/P2

· Hand protection



· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Recommendation: safety glasses with side protection shield
- · Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Colour: Whitish
Odour: Characteristic
Odour threshold: Not determined.
Melting point/freezing point: Undetermined.

 \cdot Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

• Flammability Not applicable.

· Lower and upper explosion limit

• **Lower:** 1.5 Vol % • **Upper:** 18.6 Vol %

· Flash point: Not applicable, as aerosol.

· Auto-ignition temperature: 235 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

Kinematic: 23 °C - 4 mm (ISO 2431)

· **Dynamic:** Not determined.

· Solubility

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure at 20 °C:
 5,200 hPa

· Density and/or relative density

Density at 20 °C:
 Relative density
 O.68 g/cm³
 Not determined.

(Contd. on page 7)





Printing date 03.12.2024 Version number 306 (replaces version 302) Revision: 03.12.2024

Trade name: Spray adhesive that can be separated E-COLL

(Contd. of page 6)

· Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Not determined.

· Solvent separation test:

• Organic solvents: 99.7 % • VOC (EC) % 99,60 %

· Change in condition

· Drip point:

Oxidising propertiesEvaporation rateNot determined.Not applicable.

 \cdot Information with regard to physical hazard

classes

Explosives VoidFlammable gases Void

Aerosols
 Extremely flammable aerosol. Pressurised container:

Void

May burst if heated.

 Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

· Desensitised explosives

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 8)





Printing date 03.12.2024 Version number 306 (replaces version 302) Revision: 03.12.2024

Trade name: Spray adhesive that can be separated E-COLL

(Contd. of page 7)

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:			
CAS: 141-	CAS: 141-78-6 ethyl acetate		
Oral	LD50	5,620 mg/kg (rabbit)	
Inhalative	LC50/4h	1,600 ppm (rat)	
CAS: 64742-49-0 hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cycloalkanes, < 5% n-hexane			
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>2,920 mg/kg (rat)	
		>2,000 mg/kg (rabbit)	
Inhalative	LC50/4h	>25 mg/m³ (rat)	
CAS: 108-05-4 vinyl acetate			
Oral	LD50	2,920 mg/kg (rat)	
Dermal	LD50	2,335 mg/kg (rabbit)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 9)





Printing date 03.12.2024 Version number 306 (replaces version 302) Revision: 03.12.2024

Trade name: Spray adhesive that can be separated E-COLL

(Contd. of page 8)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Toxic for aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

		<u> </u>	
	· European waste catalogue		
I	15 01 10*	packaging containing residues of or contaminated by dangerous substances	
Ī	15 01 04	metallic packaging	

- EU ---





Printing date 03.12.2024 Version number 306 (replaces version 302) Revision: 03.12.2024

Trade name: Spray adhesive that can be separated E-COLL

(Contd. of page 9)

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS, ENVIRONMENTALLY

HAZARDOUS

· IMDG AEROSOLS
· IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2.1 Gases.

· Label 2.1

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: Yes

• 14.6 Special precautions for user Warning: Gases.

• **EMS Number:** F-D,S-U

• **Stowage Code** SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS:

Category C, Clear of living quarters.

Segregation Code
 SG69 For AEROSOLS with a maximum capacity of 1

litre:

Segregation as for class 9. Stow "separated from"

class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class

2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class (Contd. on page 11)

— EU —





Printing date 03.12.2024 Version number 306 (replaces version 302) Revision: 03.12.2024

2.

Trade name: Spray adhesive that can be separated E-COLL

(Contd. of page 10)

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)Excepted quantities (EQ)Code: E0

Not permitted as Excepted Quantity

Transport categoryTunnel restriction code

· IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E0

Not permitted as Excepted Quantity

• UN "Model Regulation": UN1950, AEROSOLS, ENVIRONMENTALLY

HAZARDOUS, 2.1

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment

· Named dangerous substances - ANNEX I Methanol

(Contd. on page 12)





Printing date 03.12.2024 Version number 306 (replaces version 302) Revision: 03.12.2024

Trade name: Spray adhesive that can be separated E-COLL

(Contd. of page 11)

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

· Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at: sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH044 Risk of explosion if heated under confinement.





Printing date 03.12.2024 Version number 306 (replaces version 302) Revision: 03.12.2024

Trade name: Spray adhesive that can be separated E-COLL

(Contd. of page 12)

EUH066 Repeated exposure may cause skin dryness or cracking.

· Contact: sdb@ede.de

Date of previous version: 03.12.2024
Version number of previous version: 302

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

^{· *} Data compared to the previous version altered.