

Road and track drainage

Shaft systems

AquaTraffic® Control Flushing and inspection shaft

PE-HD flushing and inspection shaft; as shaft or start shaft; inside diameter of base body greater than 900 mm; colour: black



Technical data					
Application:	Flushing and inspection shaft for all fields of civil engineering and road engineering.				
Material / raw material:	PE-HD (polyethylene)				
Specification:	Design as shaft (180°) – with and without reducer – and start shaft				
Shaft variants / nominal connection diameters:	Shaft: Shaft with reducer: Start shaft:	2/300 300/400 300	2/400 400/500* 400	2/500 500/600 500	2/600 - 600
Effective height: [m]		1.03	1.03	1.03	1.03
Total height: [m]		1.13	1.13	1.13	1.13
Inside diameter of base body: [m]		> 0.90	> 0.90	> 0.90	> 0.90
Weight: [kg]		< 35	< 35	< 40	< 40
Technical characteristics:	Monolithic base body without weld seams; UV-resistant, extremely durable and hard-wearing; impact- and break-resistant from -20 °C to +80 °C; resistant to gasoline and diesel fuel; extension pipe can be cut to length; with integrated compensating area; watertight connection of AquaPipe pipes according to DIN 4262-1 possible; installation in traffic areas possible; connection of standard shaft covers 625 mm possible				
Miscellaneous:	CAD library and CAD details Project shafts according to order form For accessories, see product documentation "Shaft systems for road drainage"				



www.fraenkische.com

* ... deviating heights: effective height = 1.13m, total height = 1.20m