


Military Technology





Reliable Power Supply You Can Count on Worldwide

Our CEE systems comply with European industrial standards and can therefore be seamlessly used within many NATO forces. National variants usually exist only in the civilian sector, not in military power components.

Your advantages in the field:

- High mechanical durability and weather resistance
- Secure contact technology for maximum operational safety
- Modular options for mobile and stationary power supply
- Compatibility in multinational mission environments
- Long-lasting materials for extreme conditions
- Ideal for operations where reliability is a non-negotiable requirement



Reliable Power Supply According to NATO and German Armed Forces Standards

In modern military operations, robust, standard-compliant and always-available power supply is indispensable. Our CEE connectors offer the highest level of reliability and safety—even under extreme climatic, mechanical, and tactical conditions.

Thanks to the Europe-wide harmonized CEE standards, our products can be seamlessly integrated into multinational NATO infrastructures. They support international interoperability and ensure stable power distribution in mobile field camps, command posts, container systems, and logistical facilities.



Standardization in Military Environments

In addition to NATO and European industrial standards, individual countries maintain further national defense standards. In Germany, these include in particular:

VG Numbers (Defense Equipment Type Numbers)

VG numbers identify products that comply with specific military technical standards. They are issued by the German Federal Office of Bundeswehr Equipment (BAAINBw) and define:

- Technical specifications
- Dimensions and interface requirements
- Performance and quality standards

VG standards are comparable to MIL-SPEC in the United States or DEF-STAN in the United Kingdom.

Panel Mounting Socket Outlet straight 16A/32A IP67/IP69

- Screwless terminals
- Straight
- Kontex contact
- High-temperature-resistant contact carrier
- Nickel plated contacts
- Flange 75 x 75 mm
- Protection degree IP67/IP69

(Form AS)


QUICK CONNECT



13066



Ampere	Poles	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	230V 50-60 Hz	400V 50-60 Hz	400V 60 Hz	301-500Hz >50V	g
			3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	4pol 5pol 11h 11h	3pol 4pol 5pol 2h 2h 2h	
16	3	Order no. 13064 Supply no. 5935-12-... VG-type-Nr. VG 96919...	320-7272				9
			AS 013			13098	
16	4	Order no. 13928 Supply no. 5935-12-... VG-type-Nr. VG 96919...	AS 020	13633	13929	13930	170
				AS 018	AS 021	AS 022	
16	5	Order no. 13189* Supply no. 5935-12-... VG-type-Nr. VG 96919...	AS 002	13065* 300-5324	13182*	13183*	195
				AS 001	AS 003	AS 004	
32	3	Order no. 13032 Supply no. 5935-12-... VG-type-Nr. VG 96919...	AS 042			13932	245
						AS 044	
32	4	Order no. 13933 Supply no. 5935-12-... VG-type-Nr. VG 96919...	AS 025	13634	13166	13935	265
				AS 023	AS 026	AS 027	
32	5	Order no. 13297* Supply no. 5935-12-... VG-type-Nr. VG 96919...	AS 006	13066* 300-5323	13184*	13175* 321-5242	315
				AS 005	AS 007	AS 008	



Ampere Poles	16 3	16 4	16 5	32 3	32 4	32 5
a	75,0	75,0	75,0	75,0	75,0	75,0
b	75,0	75,0	75,0	75,0	75,0	75,0
c	60,0	60,0	60,0	60,0	60,0	60,0
d	60,0	60,0	60,0	60,0	60,0	60,0
Øe	5,5	5,5	5,5	5,5	5,5	5,5
f	7,0	7,0	7,0	8,0	8,0	8,0
h	35,0	35,0	35,0	50,0	50,0	50,0
i	57,0	57,0	57,0	69,0	69,0	69,0
k	77,0	83,0	93,0	98,0	98,0	107,0
Øl	45,0	75,0	55,0	60,0	60,0	60,0
m	4,0	7,0	12,0	12,0	12,0	17,0
Cond. mm² min	1,5	1,5	1,5	2,5	2,5	2,5
Cond. mm² max	4,0	4,0	4,0	10,0	10,0	10,0

4 MB 125


Panel Mounting Socket Outlet straight 63A/125A IP67/IP69

- Screw terminals
- Straight
- High-temperature-resistant contact carrier
- Box terminals
- Kontex contact
- Nickel plated contacts
- Flange 107 x 100 mm for 63A, 120 x 120 mm for 125A
- Protection degree IP67/IP69


(Form AS)



13067



Ampere	Poles	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	230V 50-60 Hz	400V 50-60 Hz	400V 60 Hz	301-500Hz >50V	g
			3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	4pol 5pol 11h 11h	3pol 4pol 5pol 2h 2h 2h	
63	3	Order no. 13186 Supply no. 5935-12-... VG-type-Nr. VG 96919...	AS 047			13927	500
						AS 049	
63	4	Order no. 13924 Supply no. 5935-12-... VG-type-Nr. VG 96919...	AS 030	13839	13925	13926	580
				AS 028	AS 031	AS 032	
63	5	Order no. 13298* Supply no. 5935-12-... VG-type-Nr. VG 96919...	AS 010	13067* 300-3603	13187*	13188* 321-5243	620
				AS 009	AS 011	AS 012	
125	3	Order no. 13840 Supply no. 5935-12-... VG-type-Nr. VG 96919...	AS 052			13923	930
						AS 054	
125	4	Order no. 13919 Supply no. 5935-12-... VG-type-Nr. VG 96919...	AS 035	13841	13920	13921	1090
				AS 033	AS 036	AS 037	
125	5	Order no. 13915 Supply no. 5935-12-... VG-type-Nr. VG 96919...	AS 015	13647	13916	13918	1210
				AS 014	AS 016	AS 017	



Ampere Poles	63 3	63 4	63 5	125 3	125 4	125 5
a	107,0	107,0	107,0	120,0	120,0	120,0
b	100,0	100,0	100,0	120,0	120,0	120,0
c	85,0	85,0	85,0	100,0	100,0	100,0
d	77,0	77,0	77,0	100,0	100,0	100,0
Øe	6,5	6,5	6,5	6,5	6,5	6,5
f	12,0	12,0	12,0	21,0	21,0	21,0
h	57,0	57,0	57,0	50,0	50,0	50,0
i	77,0	77,0	77,0	117,0	117,0	117,0
k	113,0	113,0	113,0	129,0	129,0	129,0
Øl	88,0	88,0	88,0	104,0	104,0	104,0
m	8,0	8,0	8,0	6,0	6,0	6,0
Cond. mm² min	6,0	6,0	6,0	25,0	25,0	25,0
Cond. mm² max	25,0	25,0	25,0	70,0	70,0	70,0

4 MB 134

- IEC 60309, EN 60309, VDE 0623, VG 96926
- Colour: olive-green RAL 6031-F9
- * = Approval according to VG 96919

Panel Mounting Socket Outlet angled 16A/32A IP67/IP69


- Screwless terminals
- 20° angled
- Kontex contact
- High-temperature-resistant contact carrier
- Nickel plated contacts
- Flange 85 x 85 mm
- Protection degree IP67/IP69

(Form BS)


QUICK CONNECT



12087



Ampere	Poles	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	230V 50-60 Hz			400V 50-60 Hz			400V 60 Hz			301-500Hz >50V			9 each
			3pol 6h	4pol 9h	5pol 9h	3pol 9h	4pol 6h	5pol 6h	4pol 11h	5pol 11h	3pol 2h	4pol 2h	5pol 2h		
16	3	Order no. 12085* Supply no. 5935-12-... VG-type-Nr. VG 96919...	347-4131									12280	BS 039	155	
16	4	Order no. 120025 Supply no. 5935-12-... VG-type-Nr. VG 96919...	BS 020	12699	120026	120027								175	
16	5	Order no. 12242* Supply no. 5935-12-... VG-type-Nr. VG 96919...	BS 002	12086*	12235*	12236*								200	
32	3	Order no. 12169 Supply no. 5935-12-... VG-type-Nr. VG 96919...	BS 042			120029								250	
32	4	Order no. 120030 Supply no. 5935-12-... VG-type-Nr. VG 96919...	BS 025	12700	120031	120032								275	
32	5	Order no. 12340* Supply no. 5935-12-... VG-type-Nr. VG 96919...	BS 006	12087*	12237*	12238*								315	



Ampere Poles	16 3	16 4	16 5	32 3	32 4	32 5
a	85,0	85,0	85,0	85,0	85,0	85,0
b	85,0	85,0	85,0	85,0	85,0	85,0
c	70,0	70,0	70,0	70,0	70,0	70,0
d	70,0	70,0	70,0	70,0	70,0	70,0
Øe	5,5	5,5	5,5	5,5	5,5	5,5
f	8,0	8,0	8,0	8,0	8,0	8,0
h	46,0	46,0	46,0	50,0	50,0	50,0
i	57,0	57,0	60,0	67,0	67,0	67,0
Øl	57,0	65,0	70,0	78,0	78,0	78,0
α	20°	20°	20°	20°	20°	20°
Cond. mm² min	1,5	1,5	1,5	2,5	2,5	2,5
Cond. mm² max	4,0	4,0	4,0	10,0	10,0	10,0

4 MB 124

Panel Mounting Socket Outlet angled 63A/125A IP67/IP69

- Screw terminals
- 20° angled
- High-temperature-resistant contact carrier
- Box terminals
- Kontex contact
- Nickel plated contacts
- Flange 114 x 114 mm
- Protection degree IP67/IP69


(Form BS)



12088



Ampere	Poles	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	230V 50-60 Hz			400V 50-60 Hz			400V 60 Hz			301-500Hz >50V			9 each
			3pol 6h	4pol 9h	5pol 9h	3pol 9h	4pol 6h	5pol 6h	4pol 11h	5pol 11h	3pol 2h	4pol 2h	5pol 2h		
63	3	Order no. 12239 Supply no. 5935-12-... VG-type-Nr. VG 96919...	BS 047									120034	BS 049	555	
63	4	Order no. 120035 Supply no. 5935-12-... VG-type-Nr. VG 96919...	BS 030	12953	120036	120037								590	
63	5	Order no. 12341* Supply no. 5935-12-... VG-type-Nr. VG 96919...	BS 010	12088*	12240*	12241*								630	
125	3	Order no. 12954 Supply no. 5935-12-... VG-type-Nr. VG 96919...	BS 052			120039								905	
125	4	Order no. 120041 Supply no. 5935-12-... VG-type-Nr. VG 96919...	BS 035	12955	120042	120043								965	
125	5	Order no. 12342* Supply no. 5935-12-... VG-type-Nr. VG 96919...	BS 014	12191*	12343*	12264*								1045	



Ampere Poles	63 3	63 4	63 5	125 3	125 4	125 5
a	114,0	114,0	114,0	114,0	114,0	114,0
b	114,0	114,0	114,0	114,0	114,0	114,0
c	90,0	90,0	90,0	90,0	90,0	90,0
d	90,0	90,0	90,0	90,0	90,0	90,0
Øe	5,5	5,5	5,5	6,5	6,5	6,5
f	12,0	12,0	12,0	12,0	12,0	12,0
h	65,0	65,0	65,0	82,0	82,0	82,0
i	82,0	82,0	82,0	90,0	90,0	90,0
k	92,0	92,0	92,0	92,0	92,0	92,0
Øl	92,0	92,0	92,0	105,0	105,0	105,0
m	15°	15°	15°	15°	15°	15°
Cond. mm² min	6,0	6,0	6,0	25,0	25,0	25,0
Cond. mm² max	25,0	25,0	25,0	70,0	70,0	70,0

4 MB 123

Plug 16A/32A IP67/IP69

- Screwless terminals
- High-temperature-resistant contact carrier
- Nickel plated contacts
- With protective cap
- Special gland, simultaneous cable gland and seal
- Protection degree IP67/IP69

(Form CP)


QUICK CONNECT
MULTI GRIP



Ampere	Poles	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	230V 50-60 Hz	400V 50-60 Hz	400V 60 Hz	301-500Hz >50V	g
			3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	4pol 5pol 11h 11h	3pol 4pol 5pol 2h 2h 2h	
16	3	Order no. 21220* Supply no. 5935-12-... VG-type-Nr. VG 96919...	312-5515			210403	180
			CP 017			CP 039	
16	4	Order no. 210404 Supply no. 5935-12-... VG-type-Nr. VG 96919...	CP 020	210077 CP 018	210405 CP 021	210406 CP 022	230
16	5	Order no. 21423* Supply no. 5935-12-... VG-type-Nr. VG 96919...	CP 002	21208* 300-3599 CP 001	21424* CP 003	21425* CP 004	265
32	3	Order no. 21221 Supply no. 5935-12-... VG-type-Nr. VG 96919...	CP 042			210408 CP 044	340
32	4	Order no. 210409 Supply no. 5935-12-... VG-type-Nr. VG 96919...	CP 025	210078 CP 023	210410 CP 026	210411 CP 027	380
32	5	Order no. 21426* Supply no. 5935-12-... VG-type-Nr. VG 96919...	CP 006	21209* 300-3596 CP 005	21427* 348-5139 CP 007	21380* 312-4197 CP 008	420



21208



2 MB 95


Ampere	Poles	16	16	16	32	32	32
		3	4	5	3	4	5
Ø a		70,0	78,0	86,0	94,0	94,0	101,0
b		103,5	104,0	105,5	127,0	127,0	129,5
c		153,5	154,0	160,5	187,0	187,0	193,5
d		111,0	111,0	119,0	136,0	136,0	138,5
Ø e		18,0	18,0	21,0	23,5	23,5	27,0
f		75,5	82,5	91,0	96,5	96,5	104,5
Cond. mm² min		1,0	1,0	1,0	2,5	2,5	2,5
Cond. mm² max		2,5	2,5	2,5	6,0	6,0	6,0

Plug 63A/125A IP67/IP69

- Screw terminals
- High-temperature-resistant contact carrier
- Box terminals
- Nickel plated contacts
- Special gland, simultaneous cable gland and seal
- With protective cap
- Screwless enclosure connection
- Protection degree IP67/IP69

(Form CP)


MULTI GRIP



Ampere	Poles	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	230V 50-60 Hz	400V 50-60 Hz	400V 60 Hz	301-500Hz >50V	g
			3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	4pol 5pol 11h 11h	3pol 4pol 5pol 2h 2h 2h	
63	3	Order no. 210256 Supply no. 5935-12-... VG-type-Nr. VG 96919...	CP 047			210413 CP 049	695
63	4	Order no. 210414 Supply no. 5935-12-... VG-type-Nr. VG 96919...	CP 000	210263 CP 028	210415 CP 031	210417 CP 032	755
63	5	Order no. 21428* Supply no. 5935-12-... VG-type-Nr. VG 96919...	CP 010	21210* 300-5325 CP 009	21429* CP 0011	21430* CP 012	815
125	3	Order no. 210264 Supply no. 5935-12-... VG-type-Nr. VG 96919...	CP 052			210419 CP 054	1115
125	4	Order no. 210421 Supply no. 5935-12-... VG-type-Nr. VG 96919...	CP 035	210265 CP 033	210422 CP 036	210423 CP 037	1220
125	5	Order no. 21431* Supply no. 5935-12-... VG-type-Nr. VG 96919...	CP 014	21033* 327-8595 CP 013	21432* CP 015	21433* CP 016	1330



21210



2 MB 107

Ampere	Poles	63	63	63	125	125	125
		3	4	5	3	4	5
Ø a		113,5	113,5	113,5	126,0	126,0	126,0
b		169,0	169,0	169,0	185,0	185,0	185,0
c		250,0	250,0	250,0	286,0	286,0	286,0
d		171,0	171,0	171,0	206,0	206,0	206,0
Ø e		36,0	36,0	36,0	50,0	50,0	50,0
f		112,5	112,5	112,5	125,0	125,0	125,0
Cond. mm² min		6,0	6,0	6,0	16,0	16,0	16,0
Cond. mm² max		25,0	25,0	25,0	50,0	50,0	50,0

- IEC 60309, EN 60309, VDE 0623, VG 96926
- Colour: olive-green RAL 6031-F9
- * = Approval according to VG 96919

**Appliance Inlet with flange
16A/32A IP67/IP69**

- Screw terminals
- High-temperature-resistant contact carrier
- Nickel plated contacts
- With protective cap
- Flange 85 x 85 mm
- Protection degree IP67/IP69


(Form BP)



Ampere	Poles	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	230V 50-60 Hz			400V 50-60 Hz			400V 60 Hz			301-500Hz >50V			9 each
			3pol 6h	4pol 9h	5pol 9h	3pol 9h	4pol 6h	5pol 6h	4pol 11h	5pol 11h	3pol 2h	4pol 2h	5pol 2h		
16	3	Order no. 27046* Supply no. 5935-12-... VG-type-Nr. VG 96919...	319-7028 BP 013									27286 BP 039	205		
16	4	Order no. 27287 Supply no. 5935-12-... VG-type-Nr. VG 96919...	BP 020	27204 BP 018	27288 BP 021	27289 BP 022							230		
16	5	Order no. 27104* Supply no. 5935-12-... VG-type-Nr. VG 96919...	BP 002	2702* 300-3598 BP 001	27105* BP 003	27106* BP 004							260		
32	3	Order no. 2745 Supply no. 5935-12-... VG-type-Nr. VG 96919...	BP 042			27291 BP 044							305		
32	4	Order no. 27292 Supply no. 5935-12-... VG-type-Nr. VG 96919...	BP 025	27201 BP 023	27293 BP 026	27294 BP 027							330		
32	5	Order no. 27107* Supply no. 5935-12-... VG-type-Nr. VG 96919...	BP 006	2703* 188-9997 BP 005	27108* BP 007	27043* 312-4197 BP 008							365		



2703




Ampere	16	16	16	32	32	32
Poles	3	4	5	3	4	5
a	85,0	85,0	85,0	85,0	85,0	85,0
b	85,0	85,0	85,0	85,0	85,0	85,0
c	70,0	70,0	70,0	70,0	70,0	70,0
d	70,0	70,0	70,0	70,0	70,0	70,0
Ø e	6,3	6,3	6,3	6,3	6,3	6,3
f	11,0	11,0	11,0	11,0	11,0	11,0
h	94,0	94,0	94,0	105,0	105,0	105,0
i	94,0	97,0	101,0	103,0	103,0	107,0
k	70,5	78,5	86,5	94,0	94,0	101,5
Cond. mm² min	1,0	1,0	1,0	2,5	2,5	2,5
Cond. mm² max	2,5	2,5	2,5	6,0	6,0	6,0

5 MB 31

**Appliance Inlet with flange
63A/125A IP67/IP69**

- Screw terminals
- High-temperature-resistant contact carrier
- Box terminals
- Nickel plated contacts
- With protective cap
- Flange 107 x 100 mm for 63A, 130 x 120 mm for 125A
- Protection degree IP67/IP69


(Form BP)



Ampere	Poles	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	230V 50-60 Hz			400V 50-60 Hz			400V 60 Hz			301-500Hz >50V			9 each
			3pol 6h	4pol 9h	5pol 9h	3pol 9h	4pol 6h	5pol 6h	4pol 11h	5pol 11h	3pol 2h	4pol 2h	5pol 2h		
63	3	Order no. 27267 Supply no. 5935-12-... VG-type-Nr. VG 96919...	BP 047									27295 BP 049	630		
63	4	Order no. 27296 Supply no. 5935-12-... VG-type-Nr. VG 96919...	BP 030	27268 BP 028	27297 BP 031	27298 BP 032							695		
63	5	Order no. 27109* Supply no. 5935-12-... VG-type-Nr. VG 96919...	BP 010	2704* BP 009	27110* BP 011	27045* BP 012							750		
125	3	Order no. 27269 Supply no. 5935-12-... VG-type-Nr. VG 96919...	BP 052			27299 BP 054							1010		
125	4	Order no. 27300 Supply no. 5935-12-... VG-type-Nr. VG 96919...	BP 035	27270 BP 033	27301 BP 036	27302 BP 037							1125		
125	5	Order no. 27303 Supply no. 5935-12-... VG-type-Nr. VG 96919...	BP 015	27102 300-5323 BP 014	27304 BP 016	27305 321-5242 BP 017							1220		



2704



Ampere	63	63	63	125	125	125
Poles	3	4	5	3	4	5
a	107,0	107,0	107,0	130,0	130,0	130,0
b	100,0	100,0	100,0	120,0	120,0	120,0
c	85,0	85,0	85,0	108,0	108,0	108,0
d	77,0	77,0	77,0	100,0	100,0	100,0
Ø e	6,5	6,5	6,5	6,5	6,5	6,5
f	12,0	12,0	12,0	13,0	13,0	13,0
h	142,0	142,0	142,0	134,0	134,0	134,0
i	124,0	124,0	124,0	138,0	138,0	138,0
k	113,5	113,5	113,5	126,0	126,0	126,0
l	-	-	-	23,0	23,0	23,0
Ø m	-	-	-	105,0	105,0	105,0
Cond. mm² min	6,0	6,0	6,0	16,0	16,0	16,0
Cond. mm² max	16,0	16,0	16,0	50,0	50,0	50,0

5 MB 100

**Appliance Inlet with flange
 16A/32A IP67/IP69**

- Screw terminals
- High-temperature-resistant contact carrier
- Nickel plated contacts
- With protective cap
- Flange 85 x 85 mm
- Protection degree IP67/IP69


(Form AP)



2897



Ampere	Poles	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	230V 50-60 Hz	400V 50-60 Hz	400V 60 Hz	301-500Hz >50V	g
			3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	4pol 5pol 11h 11h	3pol 4pol 5pol 2h 2h 2h	
16	3	Order no. 2892 Supply no. 5935-12-... VG-type-Nr. VG 96919...	AP 037	2893	2894		210
16	4	Order no. 2893 Supply no. 5935-12-... VG-type-Nr. VG 96919...		AP 017	2894		
16	5	Order no. 2894 Supply no. 5935-12-... VG-type-Nr. VG 96919...			AP 001		259
32	3	Order no. 2895 Supply no. 5935-12-... VG-type-Nr. VG 96919...	AP 042	2896	2897		302
32	4	Order no. 2896 Supply no. 5935-12-... VG-type-Nr. VG 96919...		AP 022	2897		
32	5	Order no. 2897 Supply no. 5935-12-... VG-type-Nr. VG 96919...			AP 005		360



Ampere Poles	16 3	16 4	16 5	32 3	32 4	32 5
a	85,0	85,0	85,0	85,0	85,0	85,0
b	85,0	85,0	85,0	85,0	85,0	85,0
c	70,0	70,0	70,0	70,0	70,0	70,0
d	70,0	70,0	70,0	70,0	70,0	70,0
Ø e	6,3	6,3	6,3	6,3	6,3	6,3
f	11,0	11,0	11,0	11,0	11,0	11,0
h	84,0	84,0	85,0	94,0	94,0	94,0
i	82,5	86,0	91,0	96,5	96,05	104,0
Ø k	70,5	78,5	86,5	94,0	94,0	101,5
Ø l	49,0	49,0	49,0	49,0	49,0	49,0
Cond. mm² min	1,0	1,0	1,0	2,5	2,5	2,5
Cond. mm² max	2,5	2,5	2,5	6,0	6,0	6,0

5 MB 73


**Appliance Inlet with flange
 63A/125A IP67/IP69**

- Screw terminals
- High-temperature-resistant contact carrier
- Box terminals
- Nickel plated contacts
- With protective cap
- Flange 110 x 106 mm for 63A, flange 120 x 120 mm for 125A
- Protection degree IP67/IP69


(Form AP)



2853



Ampere	Poles	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	230V 50-60 Hz	400V 50-60 Hz	400V 60 Hz	301-500Hz >50V	g
			3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	4pol 5pol 11h 11h	3pol 4pol 5pol 2h 2h 2h	
63	3	Order no. 28042 Supply no. 5935-12-... VG-type-Nr. VG 96919...	AP 047	28000	28043		725
63	4	Order no. 28000 Supply no. 5935-12-... VG-type-Nr. VG 96919...		AP 027	28043		
63	5	Order no. 28043 Supply no. 5935-12-... VG-type-Nr. VG 96919...			AP 009		
125	3	Order no. 28043 Supply no. 5935-12-... VG-type-Nr. VG 96919...	AP 052	28044	28045		
125	4	Order no. 28044 Supply no. 5935-12-... VG-type-Nr. VG 96919...		AP 032	28045		
125	5	Order no. 28045 Supply no. 5935-12-... VG-type-Nr. VG 96919...			AP 013		



Ampere Poles	63 3	63 4	63 5	125 3	125 4	125 5
a	110,0	110,0	110,0	120,0	120,0	120,0
b	106,0	106,0	106,0	120,0	120,0	120,0
c	90,0	90,0	90,0	100,0	100,0	100,0
d	90,0	90,0	90,0	100,0	100,0	100,0
Ø e	5,5	5,5	5,5	6,5	6,5	6,5
f	13,0	13,0	13,0	13,0	13,0	13,0
h	114,0	114,0	114,0	121,0	121,0	121,0
i	19,0	19,0	19,0	20,0	20,0	20,0
Ø k	113,5	113,5	113,5	126,0	126,0	126,0
Ø m	93,0	93,0	93,0	104,0	104,0	104,0
Cond. mm² min	6,0	6,0	6,0	16,0	16,0	16,0
Cond. mm² max	16,0	16,0	16,0	50,0	50,0	50,0

5 MB 101

- IEC 60309, EN 60309, VDE 0623, VG 96926
- Colour: olive-green RAL 6031-F9
- * = Approval according to VG 96919

Connector 16A/32A IP67/IP69

- Screwless terminals
- Kontex contact
- High-temperature-resistant contact carrier
- Nickel plated contacts
- Special gland, simultaneous cable gland and seal
- Protection degree IP67/IP69


(Form DS)

**QUICK CONNECT
MULTI GRIP**



3151

Ampere	Poles	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	230V 50-60 Hz			400V 50-60 Hz			400V 60 Hz			301-500Hz >50V			9 each
			3pol 6h	4pol 9h	5pol 9h	3pol 9h	4pol 6h	5pol 6h	4pol 11h	5pol 11h	3pol 2h	4pol 2h	5pol 2h		
16	3	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	31162* 312-5516 DS 017									310163 DS 039			180
16	4	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	310165 DS 020			31865 DS 018			310167 DS 021			310168 DS 022			215
16	5	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	31318* DS 002			31150* DS 001			31319* DS 003			31320* DS 004			255
32	3	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	31032 DS 042									310194 DS 044			325
32	4	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	310169 DS 025			31866 DS 023			310171 DS 026			310172 DS 027			355
32	5	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	31321* DS 006			31151* 300-3597 DS 005			31322* DS 007			31323* 312-4196 DS 008			410



Ampere Poles	16 3	16 4	16 5	32 3	32 4	32 5
Ø a	70,5	78,0	86,5	94,0	94,0	101,5
b	161,0	161,0	168,0	196,0	196,0	200,0
c	77,0	83,0	93,0	99,0	99,0	107,0
Ø d	18,0	18,0	21,0	23,0	23,0	27,0
Cond. mm² min	1,0	1,0	1,0	2,5	2,5	2,5
Cond. mm² max	2,5	2,5	2,5	6,0	6,0	6,0

3 MB 70

Connector 63A/125A IP67/IP69

- Screw terminals
- High-temperature-resistant contact carrier
- Box terminals
- Kontex contact
- Nickel plated contacts
- Special gland, simultaneous cable gland and seal
- Screwless enclosure connection
- Protection degree IP67/IP69


(Form DS)

MULTI GRIP



31152

Ampere	Poles	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	230V 50-60 Hz			400V 50-60 Hz			400V 60 Hz			301-500Hz >50V			9 each
			3pol 6h	4pol 9h	5pol 9h	3pol 9h	4pol 6h	5pol 6h	4pol 11h	5pol 11h	3pol 2h	4pol 2h	5pol 2h		
63	3	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	310058 DS 047									310177 DS 049			760
63	4	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	310174 DS 030			31877 DS 028			310175 DS 031			310176 DS 032			770
63	5	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	31324* DS 010			31152* 300-5326 DS 009			31325* DS 011			31326* DS 012			785
125	3	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	310059 DS 052									310179 DS 054			1160
125	4	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	310180 DS 035			310060 DS 033			310182 DS 036			310183 DS 037			1255
125	5	Order no. Supply no. 5935-12-... VG-type-Nr. VG 96919...	31327* DS 014			31027* 322-8597 DS 013			31328* DS 015			31329* DS 016			1350




Ampere Poles	63 3	63 4	63 5	125 3	125 4	125 5
Ø a	110,0	110,0	110,0	125,0	125,0	125,0
b	263,0	263,0	263,0	300,0	300,0	300,0
c	113,0	113,0	113,0	128,0	128,0	128,0
Ø d	36,0	36,0	36,0	50,0	50,0	50,0
Cond. mm² min	6,0	6,0	6,0	16,0	16,0	16,0
Cond. mm² max	16,0	16,0	16,0	50,0	50,0	50,0

3 MB 125

Domestic Panel Mounting Socket Outlet IP68

- Screw terminals
- Nickel plated contacts
- 16A/230 V~
- Flange 75 x 75 mm
- Protection degree IP68

(Form AS)



7108


18 MB 19

	Ref. no.	Supply no.	VG-type-Nr.
		5935-12-...	VG 96926...
System F	7108*	312-5115	AS 001
System E	7185		

Domestic Panel Mounting Socket Outlet IP68

- Screw terminals
- Nickel plated contacts
- 16A/230 V~
- Protection degree IP68

(Form BS)



7115


18 MB 21

	Ref. no.	Supply no.	VG-type-Nr.
		5935-12-...	VG 96926...
System F	7115*	314-4770	BS 001
System E	7186		

Domestic Plug IP68

- Screw terminals
- Nickel plated contacts
- 16A/230 V~
- With closure cap
- Protection degree IP68

(Form CP)



735


18 MB 18

	Ref. no.	Supply no.	VG-type-Nr.
		5935-12-...	VG 96926...
	735*	141-3149	CP 001

Domestic Appliance Inlet with Flange IP68

- Screw terminals
- Nickel plated contacts
- 16A/230 V~
- With closure cap
- Flange 75 x 75 mm
- Protection degree IP68

(Form AP)



753


18 MB 16

	Ref. no.	Supply no.	VG-type-Nr.
		5935-12-...	VG 96926...
	753*	340-7272	AP 001

Domestic Connector IP68

- Screw terminals
- Nickel plated contacts
- 16A/230 V~
- Protection degree IP68

(Form DS)



745

18 MB 26


	Ref. no.	Supply no.	VG-type-Nr.
		5935-12-...	VG 96926...
System F	745*	314-4771	DS 001
System E	7424		

Technical information

- IEC 60309, EN 60309, VDE 0623, VG 96926
- Colour: olive-green RAL 6031-F9
- * = Approval according to VG 96919

Domestic 3-way connector IP68

- Screw terminals
- Nickel plated contacts
- 16A/230 V~
- With closure cap, hanging bracket, cable gland
- Protection degree IP68



7400

18 MB 27

	Ref. no.	Supply no.	VG-type-Nr.
		5935-12-...	VG 96926...

System F	7400
----------	-------------

System E	7423
----------	-------------

Extension cable 16A IP67/IP69

With plug and connector 16A 5p. 6h

- Protection degree IP67/IP69



	Lenght	Ref. no.	Supply no.	VG-type-Nr.
			5935-12-...	VG 96926...

H07RN-F5G2,5	5m	810038
--------------	----	---------------

H07RN-F5G2,5	10m	810064
--------------	-----	---------------

H07RN-F5G2,5	25m	810065
--------------	-----	---------------

H07RN-F5G2,5	50m	810066
--------------	-----	---------------

Extension cable 32A IP67/IP69

With plug and connector 32A 5p. 6h

- Protection degree IP67/IP69



	Lenght	Ref. no.	Supply no.	VG-type-Nr.
			5935-12-...	VG 96926...

H07RN-F5G6	5m	810067
------------	----	---------------

H07RN-F5G6	10m	810068
------------	-----	---------------

H07RN-F5G6	25m	810069
------------	-----	---------------

H07RN-F5G6	50m	810070
------------	-----	---------------

Extension cable 63A IP67/IP69

With plug and connector 63A 5p. 6h

- Protection degree IP67/IP69



	Lenght	Ref. no.	Supply no.	VG-type-Nr.
			5935-12-...	VG 96926...

H07RN-F5G16	5m	810071
-------------	----	---------------

H07RN-F5G16	10m	810072
-------------	-----	---------------

H07RN-F5G16	25m	810073
-------------	-----	---------------

H07RN-F5G16	50m	810074
-------------	-----	---------------

Extension cable domestic type IP68

With domestic type plug and connector, system F

- Protection degree IP68



	Lenght	Ref. no.	Supply no.	VG-type-Nr.
			5935-12-...	VG 96926...

H07RN-F3G	3m	810048
-----------	----	---------------

H07RN-F3G	5m	810037
-----------	----	---------------

Technical information

- IEC 60309, EN 60309, VDE 0623, VG 96926
- Colour: olive-green RAL 6031-F9
- * = Approval according to VG 96919

Domestic 3-way connector with extension cable IP68

With domestic type plug and connector, system F

- Protection degree IP68



	Lenght	Ref. no.	Supply no. 5935-12-...	VG-type-Nr. VG 96926...
H07RN-F3G	1,5m	810053		

Closure Cap with Strap

- for CEE plugs



8337

Ampere / Poles	Ref. no.	Supply no. 5935-12-...	VG-type-Nr. VG 96926...
16A / 3p	8335		
16A / 4p	8336		
16A / 5p	8337		
32A / 3p, 4p	8338		
32A / 5p	8339		
63A / 3p, 4p, 5p	8340		
125A / 3p, 4p, 5p	8341		

Closure Cap with Strap

- for CEE connector
- for CEE Panel Mounting Socket Outlet



8330

Ampere / Poles	Ref. no.	Supply no. 5935-12-...	VG-type-Nr. VG 96926...
16A / 3p	8328		
16A / 4p	8329		
16A / 5p	8330		
32A / 3p, 4p	8331		
32A / 5p	8332		
63A / 3p, 4p, 5p	8333		
125A / 3p, 4p, 5p	8334		

Closure Cap

- for CEE plugs
- Form G



8326

Ampere / Poles	Ref. no.	Supply no. 5935-12-...	VG-type-Nr. VG 96926...
16A / 3p	8318*		G-16-3
16A / 4p	8326		G-16-4
16A / 5p	8314*		G-16-5
32A / 3p, 4p	8327		G-32-4
32A / 5p	8315*	304-8143	G-32-5
63A / 3p, 4p, 5p	8316*		G-63-5
125A / 3p, 4p, 5p	8317*		G-125-5

Closure Cap

- for CEE connector
- Form F



8309


Ampere / Poles	Ref. no.	Supply no. 5935-12-...	VG-type-Nr. VG 96926...
16A / 3p	8313*		F-16-3
16A / 4p	8324		F-16-4
16A / 5p	8309*		F-16-5
32A / 3p, 4p	8325		F-32-4
32A / 5p	8310*		F-32-5
63A / 3p, 4p, 5p	8311*		F-63-5
125A / 3p, 4p, 5p	8312*		F-125-5

Hinged Window

- Self-closing
- With touch protection
- With option for lock set



58110



30 MB 96


Module units	Dimension a	Dimension b	Ref. no.
2	55,0	40,5	580138
4	91,0	76,5	58388
6	127,0	112,5	58590
8	162,0	147,5	58110
12	234,0	220,0	58111
13	257,5	248,5	58387

Hinged Window

- Self-closing
- Without touch protection
- With option for lock set



58502



30 MB 95


Module units	Dimension a	Dimension b	Ref. no.
2	55,0	37,0	58511
4	91,0	73,0	580020
6	127,0	109,0	58503
8	162,0	144,5	58502
12	234,0	217,0	58602
13	257,5	240,0	58607

Hinged Window

- Self-closing
- With touch protection
- With option for lock set
- With mounting bracket



580143



30 MB 97

Module units	Dimension a	Dimension b	Ref. no.
2	55,0	40,5	580137
4	91,0	76,5	58517
6	127,0	112,5	580141
8	162,0	147,5	580143
12	234,0	220,0	580144
13	257,5	248,5	580145

Closure Cap

- for domestic plug
- Form H



8320

Ref. no.	VG-Typ-Nr.
8320*	H-16

Closure Cap

- für domestic connector
- Form G



8319

Ref. no.	VG-type-Nr.
8319*	G-16

Extension cable on cable reel

- cable length 25 m
- cable type H07RN-F3G2.5
- Cable reel with brake and cable guide
- Insulation class II
- Protection rating IP67

Components:

4 domestic sockets 16A, 230V, IP68
(system F - German earthing system)

Input:

1 domestic plug 16A 230V, IP68/IP69

Order no. **860127P**



Extension cable on cable reel

- cable length 50 m
- cable type H07RN-F3G2.5
- Cable reel with brake and cable guide
- Insulation class II
- Protection rating IP67

Components:

4 domestic sockets 16A, 230V, IP68
(system F - German earthing system)

Input:

1 domestic plug 16A 230V, IP68

Order no. **860156P**



Portable distribution box

- housing made of high-quality butyl rubber
- 365 × 120 mm
- Protection rating IP67
- Insulation class II

Components:

6 domestic sockets 16A, 230V, IP68
(system F - German earthing system)

Input:

5 m cable H07RN-F3G2.5 with domestic plug 16A 230V, IP68

Order no. **530097P**



Portable distribution box

- housing made of high-quality butyl rubber
- 365 × 120 mm
- Protection rating IP67
- Insulation class II

Components:

3 domestic sockets 16A, 230V, IP68
(system F - German earthing system)

Fuse:

1 RCD 25A / 0.03A, 2-pole 2 MCBs B16, 1-pole

Input:

10 m cable H07RN-F3G2.5 with domestic plug 16A 230V, IP68

Order no. **530075P**



Portable distribution box

- housing made of high-quality butyl rubber
- 455 x 146 mm
- Protection rating IP67
- Insulation class II

Components:

6 domestic sockets 16A, 230V, IP68
(system F - German earthing system)

Fuse:

3 MCBs 10A, 1p 1 surge arrester Type 3

Input:

2 m cable H07RN-F3G2.5 with domestic plug 16A 230V, IP68

Order no. **55158**



Components:

2 domestic sockets 16A, 230V, IP68
(system F - German earthing system)
2 CEE sockets 16A, 400V, 5p, 6h, IP67/IP69
2 CEE sockets 32A, 400V, 5p, 6h, IP67/IP69

Fuse:

2 RCD/MCB combinations 16A / 0.03A, 1p+N, Type A
2 MCBs 16A, 3p 2 MCBs 32A, 3p
1 RCD 40A / 0.03A, 4p 1 surge arrester Type 1+2 / 3+1 circuit

Additional equipment:


1 M12 pressure equalization element, black
1 external earthing

Input:

1 CEE appliance inlet 63A, 400V, 5p, 6h, IP67

Order no. **5204053**

EVOBOX-L
600 x 545 x 400 mm



Components:

3 domestic sockets 16A, 230V, IP68
(system F - German earthing system)
2 CEE sockets 16A, 400V, 5p, 6h, IP67/IP69
2 CEE sockets 32A, 400V, 5p, 6h, IP67/IP69
2 CEE sockets 63A, 400V, 5p, 6h, IP67/IP69
1 CEE socket 125A, 400V, 5p, 6h, IP67/IP69

Fuse:

3 MCBs 16A, 1p 2 MCBs 16A, 3p
2 MCBs 32A, 3p 2 MCBs 63A, 3p

Input:

1 CEE appliance inlet 125A, 400V, 5p, 6h, , IP67/IP69

Order no. **5203974**

EVOBOX-L
600 x 545 x 400 mm



Components:

6 domestic sockets 16A, 230V, IP68
(system F - German earthing system)

Fuse:

6 RCD/MCB combinations 16A / 0.03A, 1p+N, Type A
4 surge arresters Type 2, 1p

Additional equipment:

1 M12 pressure equalization element, black
1 external earthing

Input:

1 m cable H07RN-F5G6 with 1 CEE plug 32A, 400V, 5p, 6h, IP67/IP69

Order no. **5204046**

EVOBOX-S
400 x 340 x 350 mm



made
in
Germany



Simply. Well. Connected.

Bals Elektrotechnik GmbH & Co. KG
D-57399 Kirchhundem-Albaum
Phone: +49 27 23/771-0
Fax: +49 27 23/771-177/178
E-mail: info@bals.com
Internet: www.bals.com

Subject to technical modifications and typographical errors