

System Data Sheet



Mould control with
SP Top SL [basic]

APPLICATION INSTRUCTIONS



SUBSTRATE PREPARATION

Remove all traces of old plaster and coatings.



PREPARATION

Slightly dampen absorbent surfaces.



SUBSTRATE: ABSORBENT

Apply SP Prep as a bonding layer in a mesh pattern (coverage area 50-70%) to a layer thickness of max. 5 mm.

SUBSTRATE: SLIGHTLY ABSORBENT

Apply SP Prep, covering the surface fully (100% coverage) to a layer thickness of max. 5 mm.



APPLY CLIMATE-REGULATING PLASTER

After 24-48 hours apply SP Top SL [basic]. Min. 10 mm.



FILLER: 1ST LAYER

Once sufficiently dry, roughen the SP Top SL using a render comb. Using a toothed trowel, apply the mould control filler SL Fill Q3 to a layer thickness of 3 mm.



REINFORCEMENT

Using a smoothing trowel, embed Tex 4/100 reinforcement fabric into the filler in vertical strips, without creases and with a 10 cm overlap.



FILLER: 2ND LAYER

Apply a second layer of mould control filler SL Fill Q3 to a thickness of approx. 2mm over the reinforcement layer once it has set sufficiently. To create a fine, closed surface ready for painting, smooth the second layer with a smoothing trowel and rub if necessary once set.

COLOUR FINISH

To create surfaces with a washproof colour finish, use the solvent-free and plasticiser-free silicate interior wall paint Color SL.



NOTE:

The QR code links to the applicable Technical Data Sheet.

Please contact your specialist retailer for more information.

Technical Data Sheet



Products used

ROUGH CASTING



SP Prep

Application rate: full coverage
approx. 4 – 6 kg/m²
Art. No. 0400

SURFACE FINISH



SP Top SL [basic]

Application rate: approx.
5.6 kg/m²/cm layer thickness
Art. No. 1050

FILLER



SL Fill Q3

Application rate: approx.
1.0 kg/m²/mm layer thickness
Art. No. 2997

REINFORCEMENT



Tex 4/100

Application rate:
approx. 1.1 m²/m²
Art. No. 3880

SURFACE FINISH



Color SL

Application rate:
approx. 0.15 l/m² per coat*
Art. No. 0237

TOOLS



Rendering machine

Art. No. 4439

TOOLS



Smoothing trowel

Art. No. 4117

TOOLS



Paint Roller FC

Art. No. 4913

*Apply in 2 coats