


4.3-10 MT

F0 Connector for High-performance Communication Networks



Screw Type

- for particularly secure connections
- for use under extreme climatic conditions

Handscrew Type

- for easy installation
- with device against unintentional release

Push-Pull Type

- for fast and very easy connections
- for frequent insertion / removal

Order no.	Description	Remarks
J08091A0014	4.3-10 MT panel receptacle with flange	Type A (key up/key down)
H00080B0000	Protection cap for panel receptacle	
H00080A0000	Protection cap for panel receptacle; with chain	
U01100A0401	4.3-10 MT connector, screw type, singlemode APC, assembled on flexible fiber optic universal cable	
U01100A0402	4.3-10 MT connector, handscrew type, singlemode APC, assembled on flexible fiber optic universal cable	
U01100A0400	4.3-10 MT connector, push-pull type, singlemode APC, assembled on flexible fiber optic universal cable	
U01100A0404	4.3-10 MT connector, screw type, multimode G50/125 OM3, assembled on flexible fiber optic universal cable	
U01100A0405	4.3-10 MT connector, handscrew type, multimode G50/125 OM3, assembled on flexible fiber optic universal cable	
U01100A0403	4.3-10 MT connector, push-pull type, multimode G50/125 OM3, assembled on flexible fiber optic universal cable	
H00080B0002	Protection cap for für 4.3-10 MT connector	
L08020A2012	Fiber optic universal cable U-B(ZN)11Y 12E9/125 OS2, flexible, with PUR jacket for indoor and outdoor use, holds 12 OS2 singlemode fibers	Jacket colour: black
L08021B2012	Fiber optic universal cable U-B(ZN)11Y 12G50/125 OM3, flexible, with PUR jacket for indoor and outdoor use, holds 12 bend-insensitive OM3 multimode fibers	Jacket colour: black