



DIONE RECESSED **SPOTLIGHTS**



📌 low installation depth of only 25 mm

dimmable up to 800 lm

quick assembly thanks to quick connection box

THE PROBLEM SOLVER FOR TIGHT INSTALLATION SITUATIONS

The new DIONE series comprises elegant recessed spotlights in an aluminium housing with a particularly low installation depth – a real problem solver in the refurbishment sector.

The popular DIONE recessed ceiling lights with high-quality COB LED including reflector are integrated in an aluminium housing and have a cut-out dimension of 68 mm. While the available colours of white, silver, black, chrome and nickel harmonise with almost any type of ceiling, the real special feature of the DIONE cannot be seen when installed: The recessed spotlights are extremely space-saving when installed and require a ceiling void of just 25 or 27 mm. Here you will find the power supply unit and the quick connection box, which enables 3-pole through-wiring of several DIONE models as well as subsequent assembly as part of refurbishments.

The plug connector between the spotlight and the power supply unit allows installers to install the technology at their leisure and connect and use the spotlight conveniently once the ceiling work is complete.



IT'S THAT SIMPLE



1 - fast wiring / through-wiring on the quick connection box thanks to screwless plug-in terminals



2 - quick connection box is placed through the 68 mm cut-out in the cavity



3 - compact power supply unit is inserted into the cavity



 4 - connecting the power supply unit to the spot using a plug connector



5 - inserting the spotlight into the ceiling cut-out



6 - The result: a compact installation with a swivelling spotlight, a dimmable power supply unit and the option of throughwiring in the ceiling void - ideal for refurbishment projects.

THE RIGHT SOLUTION FOR EVERY APPLICATION

The DIONE recessed spotlights are available in the light colours 2,700K, 3,000K, 4,000K and as a dim-to-warm version [1,800-3,000K]. In addition to the IP20 version, an IP44 version is also available, making the DIONE suitable for bathrooms and other damp rooms indoors.

With this variety, the DIONE series offers recessed spotlights for a wide range of applications - from private homes and exhibition areas to guest areas in hotels and restaurants. Thanks to the wide selection of light colours and IP classes, DIONE can be flexibly integrated into any environment and covers all design requirements, from feel-good character to functional lighting.



SAVES TIME DURING ASSEMBLY

quick-release fastener, optionally fixable with screw

3-pole plug-in terminals for rigid and flexible cables up to 1.5 mm² NYM

through-wiring possible

tool-free assembly and press-fit strain relief





LIVING SPACE

- $\boldsymbol{\cdot}$ living and dining room
- children's room
- study room
- kitchen
- hallway and staircase



BUSINESS AREAS

- hotel
- gastronomy
- trade fair
- shop fitting



DAMP ROOM

- bathroom
- laundry room
- wellness centre
- indoor swimming pool











DIONE

aluminium

- dimensions H x Ø: 41 x 82 mm
- \cdot through-wiring also possible with NYM 3x 1.5 m^2
- quick installation with quick terminal
- · dimmable via phase cut-off [C-compatible]

| item | colour | colour temperature | light current | required ceiling void [min.] | EEI | price | | | |
|--|-----------------|----------------------------|---------------|------------------------------|-----|---------|--|--|--|
| 565375 | white | 👐 2700 K | 750 lm | 25 mm | E | 59,95 € | | | |
| 565376 | silver coloured | 👐 2700 K | 750 lm | 25 mm | E | 59,95 € | | | |
| 565377 | black | 👐 2700 K | 750 lm | 25 mm | E | 59,95 € | | | |
| 565379 | chrome coloured | 👐 2700 K | 750 lm | 25 mm | E | 59,95 € | | | |
| 565378 | nickel brushed | 👐 2700 K | 750 lm | 25 mm | Е | 59,95 € | | | |
| | | | | | | | | | |
| 565355 | white | 👐 3000 K | 800 lm | 25 mm | E | 59,95 € | | | |
| 565356 | silver coloured | 👐 3000 K | 800 lm | 25 mm | E | 59,95 € | | | |
| 565357 | black | 👐 3000 K | 800 lm | 25 mm | E | 59,95 € | | | |
| 565372 | chrome coloured | 👐 3000 K | 800 lm | 25 mm | E | 59,95 € | | | |
| 565371 | nickel brushed | 🚾 3000 K | 800 lm | 25 mm | E | 59,95 € | | | |
| | | | | | | | | | |
| 565358 | white | NW 4000 K | 800 lm | 25 mm | E | 59,95 € | | | |
| 565359 | silver coloured | NW 4000 K | 800 lm | 25 mm | E | 59,95 € | | | |
| 565360 | black | NW 4000 K | 800 lm | 25 mm | E | 59,95 € | | | |
| 565374 | chrome coloured | NW 4000 K | 800 lm | 25 mm | E | 59,95 € | | | |
| 565373 | nickel brushed | NW 4000 K | 800 lm | 25 mm | E | 59,95 € | | | |
| | | | | | | | | | |
| 565380 | white | ^{dtw} 1800-3000 K | 480 lm | 25 mm | F | 69,95 € | | | |
| 565381 | silver coloured | ^{dtw} 1800-3000 K | 480 lm | 25 mm | F | 69,95 € | | | |
| 565382 | black | ^{dtw} 1800-3000 K | 480 lm | 25 mm | F | 69,95 € | | | |
| 565383 | chrome coloured | ^{dtw} 1800-3000 K | 480 lm | 25 mm | F | 69,95 € | | | |
| 565384 | nickel brushed | ^{dtw} 1800-3000 K | 480 lm | 25 mm | F | 69,95 € | | | |
| | | | | | | | | | |
| $\begin{array}{c c} 220-240\\ \hline Volt \\ \hline \hline Volt \\ \hline \hline Volt \\ \hline \hline Volt \\ \hline \hline Vo$ | | | | | | | | | |





DIONE IP44

aluminium

- dimensions H x Ø: 41 x 82 mm
- \cdot through-wiring also possible with NYM 3x 1.5 m^2
- quick installation with quick terminal
- · dimmable via phase cut-off [C-compatible]

| item | colour | colour temperature | light current | required ceiling void [min.] | EEI | price | | | |
|---|-----------------|----------------------------|---------------|------------------------------|-----|---------|--|--|--|
| 565388 | white | 🚾 2700 K | 750 lm | 27 mm | Е | 64,95 € | | | |
| 565389 | silver coloured | 👐 2700 K | 750 lm | 27 mm | Е | 64,95 € | | | |
| 565390 | black | 👐 2700 K | 750 lm | 27 mm | Е | 64,95 € | | | |
| 565391 | chrome coloured | 👐 2700 K | 750 lm | 27 mm | Е | 64,95 € | | | |
| 565392 | nickel brushed | 👐 2700 K | 750 lm | 27 mm | Е | 64,95 € | | | |
| | | | | | | | | | |
| 565393 | white | 🚾 3000 K | 800 lm | 27 mm | Е | 64,95 € | | | |
| 565394 | silver coloured | 🚾 3000 K | 800 lm | 27 mm | Е | 64,95 € | | | |
| 565395 | black | 🚾 3000 K | 800 lm | 27 mm | Е | 64,95 € | | | |
| 565396 | chrome coloured | 🚾 3000 K | 800 lm | 27 mm | Е | 64,95 € | | | |
| 565397 | nickel brushed | 👐 3000 K | 800 lm | 27 mm | Е | 64,95 € | | | |
| | | | | | | | | | |
| 565398 | white | NW 4000 K | 800 lm | 27 mm | Е | 64,95 € | | | |
| 565399 | silver coloured | NW 4000 K | 800 lm | 27 mm | Е | 64,95 € | | | |
| 565400 | black | NW 4000 K | 800 lm | 27 mm | Е | 64,95 € | | | |
| 565401 | chrome coloured | NW 4000 K | 800 lm | 27 mm | Е | 64,95 € | | | |
| 565402 | nickel brushed | NW 4000 K | 800 lm | 27 mm | Е | 64,95 € | | | |
| | | | | | | | | | |
| 565403 | white | ^{dtw} 1800-3000 K | 480 lm | 27 mm | F | 74,95 € | | | |
| 565404 | silver coloured | ^{dtw} 1800-3000 K | 480 lm | 27 mm | F | 74,95 € | | | |
| 565405 | black | ^{dtw} 1800-3000 K | 480 lm | 27 mm | F | 74,95 € | | | |
| 565406 | chrome coloured | ^{dtw} 1800-3000 K | 480 lm | 27 mm | F | 74,95 € | | | |
| 565407 | nickel brushed | dtw 1800-3000 K | 480 lm | 27 mm | F | 74,95 € | | | |
| [] [| | | | | | | | | |
| $\begin{array}{c c} 220-240\\ \hline Volt \\ \hline \hline Volt \\ \hline \hline Volt \\ \hline Volt \\ \hline \hline Volt \\ \hline \hline Volt \\ \hline \hline Volt \\ \hline $ | | | | | | | | | |





DEKO-LIGHT Elektronik Vertriebs GmbH Auf der Hub 2 76307 Karlsbad

T +49 7248 9271 600 F +49 7248 9271 650

exporteu@deko-light.com deko-light.com shop.deko-light.com



MARC'S EXPERT ADVICE:

»The DIONE recessed ceiling spotlights are super quick and easy to install for both refurbishments and new buildings. Thanks to the sophisticated design, installation problems are a thing of the past.«